

HES SERIES (High Efficiency) TUBE-ICE MACHINE

HES30 & HES40




The HES Series with a capacity range of 3000 to 4000 pounds of ice per day is the preferred choice of ice machine for thousands of food service applications worldwide.


Heavy-duty industrial construction, automatic operation, energy efficiency and the best warranty in the business make the Vogt HES Series the only "clear" choice for your ice making needs.

HES Standard Features:

- **¥** 25 Year Evaporator Warranty
- **¥** Voltage 208/230v.,3p.,60hz.
- **¥** Refrigerant 404a
- **★** Cutter for cylinder (default) or crushed ice operation
- **★** Copeland Performance Alert power monitor
- **★** Electronic ice bin thermostat
- **¥** Stainless steel casings
- **¥** Integral drip pan
- **★** Self-Diagnostic indicator light
- **★** Water-cooled or remote air-cooled operation
- **¥** PLC Controls

HES Tube-Ice Available in Two Ice Sizes:





¥ Voltage - 460v.,3p.,60hz.¥ Voltage - 400v.,3p.,50hz.

HES Series Options:

- ¥ Voltage 200v.,3p.,50hz.
- High ambient air-cooled condenser
- **★** Electro-fin coated condenser
- ★ High pressure (200psig) water condenser/regulator
- **★** Casing security screws (Correctional usage)
- **★** Cutter for 1-1/2" long ice
- ▼ Remote switch box
- **¥** Flush valve assembly
- * "CE" Approval (400v, 50hz only)
- **★** Canadian Registration Number (CRN)
- **¥** Export crating (ISPM-15 Rated)

Energy usage based on makeup water temperature of 70 $^{\rm o}$ F. (21 $^{\rm o}$ C.), ambient (air) temperature of 90 $^{\rm o}$ F. (32 $^{\rm o}$ C.).

Capacity rating is average for the model.

Individual machines may vary +/- 5%.

Capacity based on ambient (air) temperature of 90 ° F. (32 ° C.).

Capacity reduced 17% for 50hz. operation.

Makeup water usage includes 20% blowdown.

	Machine Capacity						Water Usage				Energy Usage	
	Make-Up Temperature						Ice M	Making Condenser			(KWH/100 lbs)	
	50°F	(10°C)	70°F (2	21°C)	90°F	(32 °C)	Gal/	Liters/	Gal/	Liters/	Water	Air
Model	Lbs	Kg	Lbs	Kg	Lbs	Kg	100lbs	100lbs	100lbs	100lbs	Cooled	Cooled
HES-30S	3070	1393	2750	1247	2300	1043	14.5	54.9	220	833	3.02	3.74
HES-30M	2690	1220	2400	1089	2010	912			341	1291	3.30	4.38
HES-40S	4070	1846	3620	1642	3230	1465			171	647	3.07	3.85
HES-40M	3565	1617	3170	1438	2830	1284			402	1522	3.45	4.41

Vogt Ice LLC

1000 W. Ormsby Avenue Louisville, KY 40210 (800) 853-8648, (502) 635-3000 info@vogtice.com


















HES SERIES (High Efficiency) TUBE-ICE MACHINE

HES30 & HES40







NOTE: MACHINE FOOTPRINT WITHOUT CASINGS: 40" X 26" X 54"

		Ice Machine Electrical Information					Motor Information						
		Water Cooled		Air Cooled			Water	Cutter	Condenser	Compressor	Ship	ping	
			Min.	Max. Fuse		Min.	Max. Fuse	Pump	Motor	Fan Motor(s)		We	ight
Model	Voltage	F.L.A.	Ampacity	Size (Amps)	F.L.A.	Ampacity	Size (Amps)	H.P.				Lbs	Kg
HES-30	208/230V, 3ph, 60hz	21.6	25.4	45	29.6	33.4	50						
	460V, 3ph, 60hz	10.7	12.6	20	11.6	13.5	20			2@1/2	4	1250	567
	200V, 3ph, 50hz	22.6	26.4	40	30.6	34.4	45						
	400V, 3ph, 50hz	11.2	13.1	20	12.1	14.9	20	1/3	1/2				
HES-40	208/230V, 3ph, 60hz	27.3	32.5	55	35.3	40.5	65	1/3	1/2				
	460V, 3ph, 60hz	14.8	17.7	25	15.7	19.5	30			2@1/2	6	1275	578
	200V, 3ph, 50hz	28.3	33.5	50	36.3	41.5	60						
	400V, 3ph, 50hz	15.3	18.2	25	16.2	20.0	30						



Line Size Connections								
lce Maki	3/8" FPT							
Drain Connections	Overflow	3/4" FPT						
	Drip Pan	3/4" FPT						
* Condenser Water	HES-30	3/4" FPT						
Inlet and Outlet	HES-40	1" FPT						

^{**} See service manual or air-cooled installation instruction packet for sizing discharge and return piping.

NOTE: * WATER COOLED MACHINE / ** A IR COOLED MACHINE

Operating Conditions

The ice machine shall not be subjected to an atmospheric temperature lower than 50 $^{\circ}$ F. (10 $^{\circ}$ C.) nor higher than 90 $^{\circ}$ F. (32 $^{\circ}$ C.) without effect on performance. Water for condensing or ice making purposes shall be non-corrosive.

The water shall be at a constant pressure no less than 30lbs. at the ice machine location. The condition of the water to make satisfactory ice shall be the responsibility of the purchaser.